

# Receptacles

# 1,5 (.060) Type series terminals



Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Steel Ni	Material thickness (mm)	Parts x reel
					00	01	02	30	31	32	24		
	One key												
	<b>= &lt; 0,5</b> (= < 20)	= < 1,6	1,6x0,8	<b>4487.</b>	•	•		•	•			0,25	9.000
<b>0,75-1,25</b> (18-16)	= < 2,4	<b>4489.</b>		•	•		•	•			6.000		

Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Steel Ni	Material thickness (mm)	Parts x reel
					00	01	02	30	31	32	24		
	Two keys												
	<b>= &lt; 0,5</b> (= < 20)	= < 1,6	1,6x0,8	<b>4491.</b>	•	•		•	•			0,25	9.000
<b>0,75-1,25</b> (18-16)	= < 2,4	<b>4493.</b>		•	•		•	•			6.000		



Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Cu. Alloy Pre-Sn	Material thickness (mm)	Parts x reel
					00	01	02	30	31	32	81		
	Standard insulation												
	<b>0,35-0,5</b> (22-20)	STD	1,5x0,8	<b>8681.</b>							•	0,25	6.000
	<b>0,5-1</b> (20-18)			<b>8683.</b>							•		5.000
<b>1-1,5</b> (18-16)	<b>8685.</b>										•		

Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Cu. Alloy Pre-Sn	Material thickness (mm)	Parts x reel
					00	01	02	30	31	32	81		
	SEAL insulation												
	<b>0,35-0,5</b> (22-20)	SEAL	1,5x0,8	<b>8677.</b>							•	0,25	5.000
<b>0,75-1</b> (18)	<b>8679.</b>									•			

# Special receptacles

# 1,5 (.060) Type series terminals



Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Steel Ni	Material thickness (mm)	Parts x reel
					00	01	02	30	31	32	24		
	0,5-0,75 (20-18)	1,5-1,9		8621.				•	•			0,25	6.500
	0,75-1 (18)	1,9-2,4		8623.				•	•				
	1-1,5 (18-16)			8625.				•	•				
	0,5-0,75 (20-18)	3,4 SEAL		8601.				•	•			0,25	4.000
	1-1,5 (18-16)			8603.				•	•				
	0,5-0,75 (20-18)	1,5-1,9		8627.					•			0,25	5.500
	0,75-1 (18)	1,9-2,4		8629.					•				5.000
	1-1,5 (18-16)			8631.					•				
	0,5-1 (20-18)	1,5-2,1		8633.					•			0,25	8.000
	1,5-1,75 (16-14)	1,9-2,4		8607.					•				6.500
	2,5 (14)			8609.					•				6.000



Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Steel Ni	Material thickness (mm)	Parts x reel
					00	01	02	30	31	32	24		
	= < 0,5 (= < 20)	= < 1,6	0,8	<b>6487.</b>	•	•		•	•			0,25	9.000
	<b>0,75-1,25</b> (18-16)	= < 2,4		<b>6489.</b>	•	•		•	•				
	<b>0,75-1</b> (18)	2,2 Máx.	0,8	<b>6486.</b>	•	•			•			0,4	5.500
	<b>1,5</b> (16)			<b>6488.</b>	•	•			•				
	<b>0,75-1</b> (18)	3,4 SEAL	0,8	<b>6490.</b>	•	•			•			0,4	3.500
	<b>1,5</b> (16)			<b>6491.</b>	•	•			•				



Figure	Wire size mm <sup>2</sup> (AWG)	Ø Insulation (mm)	Tab thickness (mm)	Part number	Brass	Brass Pre-Sn	Brass Sn	Bronze	Bronze Pre-Sn	Bronze Sn	Cu. Alloy Pre-Sn	Material thickness (mm)	Parts x reel	
					00	01	02	30	31	32	51			
	0,35-0,5 (22-20)	STD	1,5x0,8	6481.							•	0,3	7.000	
	0,5-1 (20-18)			6483.									•	6.000
	0,5-1,5 (20-16)			6485.										•
	0,35-0,5 (22-20)	SEAL	1,5x0,8	6477.							•	0,3	5.000	
	0,75-1 (18)			6479.										•

